ADDENDUM TWO

BLACKFEET COMMUNITY HOSPITAL EXPANSION & RENOVATION

PHASES 1 & 2
Browning, Montana

CONTRACT: 102-96-0005
ORDER: 006
PROJECT: BI7BF079H7

LAO No. C168

PREPARED FOR

DHHS/PHS/IHS/ENGINEERING SERVICES

2201 SIXTH AVENUE, M/S RX-24

SEATTLE, WASHINGTON 98121-2500



Addendum Two

BLACKFEET COMMUNITY HOSPITAL

Expansion and Renovation – Phases 1 & 2 Browning, Montana

C168

Modify the drawings and specifications for the BLACKFEET COMMUNITY HOSPITAL, Expansion and Renovation, Phases 1 and 2, dated 19 July 1999 to reflect the following items. Incorporate these changes, clarifications, and additions into the contract documents and bids for this project.

PART 1: SPECIFICATIONS

A. SECTION 02200, EARTHWORK.

The Government has identified three areas which may be used for import borrow. Areas 1 and 3 are located generally at an approximate distance of 900 feet (275 m) northeast of the hospital. Area 2 is generally located approximately 500 feet (150 m) northwest of the hospital. Refer to attached sketch CX-1. The contractor shall coordinate borrow activities with the owner. At the end of borrow activities, leave the area with a uniform grade without piles, trenches, or pits.

B. SECTION 05500, METAL FABRICATIONS.

Add subsection 2.11 as follows:

- 2.11 HARDWARE FOR SLIDING CANTILEVER GATES
 - A. General: Provide complete industrial hardware for cantilever sliding metal gates.
 - B. Track: Cold-rolled galvanized steel section.
 - C. Rollers: Steel wheels with precision ball bearings mounted on height-adjustable ground plates. All parts to be galvanized or painted.
 - D. End Rollers: Steel ballbearing wheel with clamp plate for rail-end fixing. All parts to be galvanized.
 - E. End Guide: Wall or post-fixed pair of adjustable nylon guide rollers for each gate section. Steel parts are to be galvanized.
 - F. Manufacturers: Manufacturers include but are not limited to:
 - 1. P. C. Henderson, Ltd.
 - 2. Gunnebo Troax AB.

C. SECTION 06100, ROUGH CARPENTRY.

Subsection 3.4.A should read as follows:

General: Install gypsum sheathing board according to manufacturer's instructions and GA-253 "Application of Gypsum Sheathing." Fasten gypsum sheathing to supports to comply with manufacturer's recommended spacing and referenced fastening schedule. Keep perimeter fasteners 3/8 inch (10 mm) from edges and ends of units. Fit units tightly against each other and around openings.

- D. SECTION 06100, ROUGH CARPENTRY.
 Renumber subsection 0.1 TAPE AND SEALANT APPLICATION to correspond with Part 3 requirements.
- E. SECTION 06100, ROUGH CARPENTRY.

 Delete subsection 3.5 FIBER BOARD SHEATHING in its entirety.
- F. SECTION 06402, INTERIOR ARCHITECTURAL WOODWORK. Add subsection 3.4 as follows.
 - 3.4 COLOR SELECTIONS
 - A. Plastic Laminate
 - 1. PL1 Formica, Veneer, #4402, White Oak.
 - PL2 Formica, Veneer, #4008, Antique Cherry.
 - PL3 Nevamar, #S-5-52T.
 - PL4 Formica, #7214-58.
 - PL5 Nevamar, #FS-2-2HL.
 - PL6 Wilsonart, #D47-60.
 - PL7 Formica, #842-58.
 - PL8 Nevamar, #FS-1-IT.
 - PL9 Nevamar, #MR-5-6T.
 - PL10 Wilsonart, #D48-60.
 - PL11 Nevamar, #PT-5-1SM.
 - PL12 Wilsonart, #D7806-60.
 - PL13 Wilsonart, #4740-60.
 - PL14 Wilsonart, #D476-60. PL15 Wilsonart, #4720-60.
 - PL16 Nevamar, #S-5-35T.
 - PL17 Nevamar, #FS-2-3T.
 - PL18 Formica, #7226-58.
 - PL19 Wilsonart, #D466-60.
 - PL20 Nevamar, #AL-3-1T.
 - PL21 Nevamar, #ES-2-1T.
 - B. Solid Surface Material
 - 1. SS1 Avonite, Kaleidoscope, K3-8200.
 - SS2 Corian, Prairie, Summit.
 - SS3 Corian, Savannah, Magna.
 - SS4 Corian, Sage, Lustra Collection.
- G. SECTION 09310, CERAMIC TILE.

Subsection 3.7.A.1.a.

Replace the phrase "Six (6) colors to be selected" with the following color selections:

- T1a: #A233 Sand Bisque.
- T1b: #A580 Oceana.
- T1c: #A890 Ebony.
- T1d: #A634 Terra Cotta.
- T1e: #A260 Pebble.

T1f: #A215 Empress White.
T1g: #A480 Hunter Green.
T1h: #A780 Plum mauve.
T1i: #A380 Sunflower.
T1j: #A400 Bayberry.

H. SECTION 09310, CERAMIC TILE.

Subsection 3.8.A.1.a.

Replace the phrase "Six (6) colors to be selected" with the following color selections:

CT1a: #A260 Pebble.

CT1b: #A634 Terra Cotta. G. CT1c: #A480 Hunter Green. G.

CT1d: #A380 Sunflower. G.

CT1e: #A400 Bayberry. G.

CT1f: #A580 Oceana. G.

CT1g: #A780 Plum mauve. G.

I. SECTION 09310, CERAMIC TILE.

Subsection 3.8.B.1.a.

Replace the phrase "Four (4) colors to be selected" with the following color selections:

CT2a: #IG17 Turquoise.

CT2b: #IG12 Ruby.

CT1c: #IG15 Sapphire.

J. SECTION 09653, RESILIENT WALL BASE AND ACCESSORIES.

Subsection 3.5.A.1.

Replace the phrase "Available Products: as follows" with the following subsection.

1. Available Products: Johnsonite, Rubber Wall Base.

K. SECTION 09653, RESILIENT WALL BASE AND ACCESSORIES.

Subsection 3.5.A.2.

Replace the phrase "Color and Pattern: As selected from manufacturer's full range of colors and pattern produced for rubber wall base complying with requirements indicated" with the following subsection.

2. Color and Pattern:

R1: DC-85 Burgundy, 4" (100 mm).

R2: DC-49 Beige, 4" (100 mm).

R3: DC-49 Beige, 4" (100 mm).

R4: DC-49 Beige, 6" (150 mm).

R5: DC-45 Sandalwood, 4" (100 mm).

L. SECTION 09653, RESILIENT WALL BASE AND ACCESSORIES. Subsection 3.5.B.1.

Replace the phrase "Available Products: as follows" with the following subsection.

- 1. Available Products: Johnsonite, Rubber Stair Treads and Risers.
- M. SECTION 09653, RESILIENT WALL BASE AND ACCESSORIES. Subsection 3.5.B.2.

Replace the phrase "Color and Pattern: As selected from manufacturer's full range of colors and pattern produced for rubber stair treads and accessories complying with requirements indicated" with the following subsection.

- 1. Color and Pattern: #49 Beige.
- N. SECTION 09653, RESILIENT WALL BASE AND ACCESSORIES. Subsection 3.5.C.1.

Replace the phrase "Available Products: as follows" with the following subsection.

- 1. Available Products: Johnsonite, Rubber transitional moldings.
- O. SECTION 09653, RESILIENT WALL BASE AND ACCESSORIES. Subsection 3.5.C.2.

Replace the phrase "Color and Pattern: As selected from manufacturer's full range of colors and pattern produced for rubber stair treads and accessories complying with requirements indicated" with the following subsection.

- 1. Color and Pattern: #49 Beige to be used with sheet vinyl flooring materials, #45 Sandalwood to be used at wood look sheet vinyl flooring (V5), #85 Burgundy to be used at carpet flooring materials.
- P. SECTION 09900, PAINTING.

Add subsection 3.8 as follows.

- 3.8 COLOR SELECTIONS
 - A. Color Selections are noted as Sherwin Williams' color numbers for reference only. All other approved manufacturers are required to match colors.
 - B. Colors
 - 1. P1: Sherwin Williams, #1115 Irish Cream.
 - P2: Sherwin Williams, #1073 Dusting Powder.
 - P3: Sherwin Williams, #1116 Vellum.
 - P4: Sherwin Williams, #1072 Illusive Fawn.
 - P5: Sherwin Williams, #1115 Irish Cream.
 - P6: Sherwin Williams, #1319 Mystique.
 - P7: Sherwin Williams, #1197 Tempting Teal.
 - P8: Sherwin Williams, #1187 Moonstone.
 - P9: Sherwin Williams, #1274 Post-Modern Mauve.
 - P10: Sherwin Williams, #1552 Baroque Plum.
 - P11: Sherwin Williams, #1113 Raffia Basket.
 - P12: Sherwin Williams, #1194 Mystery Green.
- Q. SECTION 15140, PIPING APPLICATIONS.

Add the following under Part 3, paragraph 3.2:

- C. Underground Domestic Water Piping: Use the following materials:
 - 1. NPS 1-1/2" (DN 40) and smaller: Soft copper tube, Type K (Type A); copper, solder-joint pressure fittings; and soldered joints.

PART 2: DRAWINGS

A. C1.1, SITE TOPOGRAPHY.

Reroute the sanitary sewer line from manhole at rim elevation 4405.67 to the manhole to the northwest. This line goes east-southeast from the manhole.

B. 1/L3.2, ENLARGED COURTYARD PLAN.

Instead of the swinging gates as shown, the gates at the entrance to the equipment yard are bi-parting cantilever sliding gates. Refer to attached sketch LX-1.

C. 11/L4.1, GATE AND SCREEN ELEVATION.

Instead of the swinging gates as shown, the gates at the entrance to the equipment yard are to be bi-parting cantilever sliding gates. Refer to changes for specification section 05500 for hardware requirement. Refer to attached sketch LX-2.

D. 19/A0.5, DOOR HEAD AT VESTIBULE.

Continue the interior vapor barrier along the horizontal offset/soffit. Overlap and seal the vapor barrier where it meets the walls. The line near the bottom of the assembly represents an air-infiltration barrier.

E. 8/A0.6, WINDOW HEAD.

Continue the interior vapor barrier along the horizontal offset/soffit. Overlap and seal the vapor barrier where it meets the walls. The line near the bottom of the assembly represents an air-infiltration barrier.

F. 11/A4.1, STAIR #2 & #4 SECTION.

The dimension for the pickets in the guardrail and fence is to be 1-inch (25 mm) diameter steel tube. This is the same for the site fence shown on 21/L3.2, WALL ELEVATION.

G. 1/A5.21, NORTH LOBBY FLOOR PLAN.

Replace the custom turtle floor pattern in Sub-Waiting 1502 with a morning star pattern. Refer to attached sketch AX-2 for revisions to custom floor patterns.

H. A7.2, FINISH PLAN – AREA A.

Refer to updated plan with revisions dated 1 September 1999.

I. A7.3, FINISH PLAN – AREA B.

Refer to updated plan with revisions dated 1 September 1999.

- J. A7.4, FINISH PLAN AREA C. Refer to updated plan with revisions dated 1 September 1999.
- K. M5.1, ENLARGED MECHANICAL ROOM PLAN.Refer to Plumbing plans, P2.1 through P3.3, for additional pipe legend.
- L. M5.1, ENLARGED MECHANICAL ROOM PLAN.
 Change detail reference for piping support at southeast corner of room 1295 to 3/M5.1.
- M. E3.2, AREA B POWER PLAN.
 Run conduit for x-ray controls next to view windows adjacent to doors/doorway at rooms 1419, 1429, and 1431 (Pan, Operatory, and Operatory). Reference equipment items 317 and 323 in schedule of owner furnished equipment on sheet T2.1.
- N. E4.1, AREA A SPECIAL SYSTEMS.

 Revise conduit run from security cameras centered in the ceiling between Lobby 1505 and Waiting 1509 to terminate on the north side of the wall between Waiting 1509 and Visit Planning 1511.

PART 3: EXTERIOR COLOR SCHEDULE


NOTE: Manufacturer's names and alternates are used for color reference only. All other approved manufacturers are required to match colors.


ITEM	COLOR	MANUFACTURER	REMARKS		
SOUTH ENTRY AREA					
Field tile	Peach Fuzz	Trenwyth Industries	structural glazed facing		
Alternate Field base tile	Rose Pink A Canella	Spectra Glaze II Trenwyth Industries	prefaced concrete block structural glazed facing		
Alternate	Autumn Oakleaf	Premier Block Corp.	polished concrete block		
Accent stripe	Cream 5000	Elgin-Butler	structural glazed facing		
tile Alternate tile	Ivory	Trenwyth Industries	structural glazed facing		
Accent block #1 Alternate Accent block #2 Alternate Accent block #3 Alternate	Ebony Special Brown Ivory Custom Clear Warm Spice Deep Sierra Red	Astra-glaze sw Spectra Glaze II Astra-glaze sw Spectra Glaze II Astra-glaze sw Spectra Glaze II	glazed facing tile prefaced concrete block glazed facing tile prefaced concrete block glazed facing tile prefaced concrete block		
Window frames Doors & frames Glass	Dark Ivy 7005 Dark Ivy 7005 Solex (green)	Pittsburgh Paints Pittsburgh Paints PPG	Kynar Kynar sungate 100		
Column base Column tube	Brick Red Morning Glory 20	Davis Colors 194	4 lbs. 160 Pittsburgh Paints		
Roof edge flashir	ng SW2119	Umbrella Black	Sherwin Williams		
Canopy skylight Canopy frame	Crystal Texas Sage	Kalwall Citadel Architectural	Products		

Expansion ar	d Renovation	- Phases 1	& 2
--------------	--------------	------------	-----

ITEM	COLOR	MANUFACTURER	REMARKS			
NORTH ENTRY AREA						
Field tile tile	Peach Fuzz	Trenwyth Industries	structural glazed facing			
Alternate Field base tile	Rose Pink A Canella	Spectra Glaze II Trenwyth Industries	preface concrete block structural glazed facing			
Alternate	Autumn Oakleaf	Premier Block Corp.	polished concrete block			
Accent stripe	Cream 5000	Elgin-Butler	structural glazed brick			
Accent block #1 Alternate Accent block #2 Alternate Accent block #3 Alternate	Ebony Special Brown Ivory Custom Clear Warm Spice Deep Sierra Red	Astra-glaze sw Spectra Glaze II Astra-glaze sw Spectra Glaze II Astra-glaze sw Spectra Glaze II	glazed facing tile prefaced concrete block glazed facing tile prefaced concrete block glazed facing tile prefaced concrete block			
Window frames Doors & frames Glass	Dark Ivy 7005 Dark Ivy 7005 Solex (green)	Pittsburgh Paints Pittsburgh Paints PPG	Kynar Kynar sungate 100			
Column base Column tube	Brick Red Morning Glory 20	Davis Colors 94	4 lbs. 160 Pittsburgh Paints			
Roof edge flashing SW2119		Umbrella Black Sherwin Williams				
Canopy skylight Canopy frame	Crystal Texas Sage	Kalwall Citadel Architectural	Products			

ITEM	COLOR	MANUFACTURER	REMARKS		
TYPICAL EXTERIOR Field stucco Accent stripe	WALL AREA Adobe Accent 139 Pure Cream 386A	3	EIFS EIFS		
Base block Alternate Base accent Alternate	Mojave Autumn Oakleaf Warmtone Warm Stone	Anchor Block Premier Block Corp. Anchor Block Premier Block Corp.	burnished concrete block polished concrete block burnished concrete block polished concrete block		
Accent tile #1 Accent tile #2	Deep Grey 599 Transparent Saha ceramic tile		ceramic tile Buchtal Corp.		
Accent tile #3	Distinct Apricot 547 ceramic tile		Buchtal Corp.		
Window frames Doors & frames Glass	Dark Ivy 7005 Dark Ivy 7005 Solex (green)	Pittsburgh Paints Pittsburgh Paints PPG	Kynar Kynar sungate 100		
Roof edge flashir	ng SW2119	Umbrella black	Sherwin Williams		





ENLARGED COURTYARD PLAN L3.2 NOT TO SCALE

	LA Olson & Associates, Inc.	PROJECT HEAVER						
	111111	C168			ž	DATE	DESCRIPTION	DATE
		SCALE:	S# MUDNADDA	BLACKFEET COMMUNITY HOSPITAL	Δ	9/1/89	VOOCHOINI 3	09/01/99
1		AT.S.		EXPANSION & RENOVATION	\triangle		11. 11. No.	SHEET NUMBER
			LANDSCAPE SHT. L3.2	PHASES 1 & 2	\mathcal{A}			
	2526 CRING ANCHE, P.O. BOX 20257 (401)056-7244 FAZ: (401)055-4407	CYAMN BY:	ENLARGED COURTYARD PLAN	BROWNING, MONTANA	4			LX-1
	BELINCS, MONTANA 59107		SOUTH THE TENT	DUCAUMO, WOMINA	$\angle \Delta$		Per School Control of the Control	:

